

A.F.F.F. FOAM

STORED PRESSURE CONTROLLED DISCHARGE EXTINGUISHERS



Controllable discharge CE Certified fire Extinguishers manufactured to I.S. EN 3, Precision engineered with brass valve and steel cylinder which is electro static paint finished to a very high standard.

CLASSES OF FIRES, A.B.

A

Paper, Wood, & General
Combustable Fires requiring
cooling and quenching

B

Burning liquids,
petrol, alcohol,
paint, oil, grease.



A MEMBER OF:
FIRE INDUSTRY ASSOCIATION OF IRELAND

ANSUL AUTHORISED AGENT

Tel (074) 9156 300 Fax (074) 9156 572

Mobile (086) 2554789

e-mail: eddie@abcfire.ie

KESHENDS, NEWTOWNCUNNINGHAM, CO DONEGAL

A.F.F.F. FOAM SPRAY FIRE EXTINGUISHERS

TECHNICAL DETAILS

MODEL	FO 6	FO 9
CAPACITY	6 LITRE	9 LITRE
NECK RING	INTEGRAL M30 X 1.5 INTERNAL THREAD	
HEAD CAP	BRASS-STEEL LEVERS WITH GAGUE	
HOSE	13mm bore black 5 braided PVCwith spray nozzles	
EXTERNAL FINISH	Phosphate / electro-static red enamel finish to BS 381C RED	
INTERNAL FINISH	Phosphate and Polythene	
WEIGHT FULL	9.20 KG	13.30 KG
TEST PRESSURE (BAR)	30	30
WORKING TEMPRATURE	0 to +60 C	0 to +60C
SPECIFICATION	Manufactured to ISEN 3 and Certified to CE 0029	
FILL	94% Water 6% Foam AFFF	

PERFORMANCE DETAILS

DISCHARGE RANGE(M)	6	6
DURATION (SEC)	60	60
FIRE RATING	13A 183B	21A 183B

OVERALL DIMENSIONS

HEIGHT (mm)	520	540
DIAMETER (mm)	150	180

PACKING SPECIFICATION

INDIVIDUALLY BOXED

ALL FIRE EXTINGUISHERS SUPPLIED FILLED

AND CHARGED WITH OXYGEN

FREE NITROGEN OVER GAS.

A.B.C. FIRE PROTECTION