

CARBON DIOXIDE, CO₂

STORED PRESSURE CONTROLLED DISCHARGE EXTINGUISHERS



Controllable discharge CE Certified fire Extinguishers manufactured to I.S. EN 3, Precision engineered with brass valve and aluminium cylinder which is electro static paint finished to a very high standard.

CLASSES OF FIRES, B.C.

B

Burning liquids,
petrol, alcohol,
paint, oil, grease.

C

Gas Fires,
Methane, propane,
butane, acetylene.



A MEMBER OF:
FIRE INDUSTRY ASSOCIATION OF IRELAND

ANSUL AUTHORISED AGENT

Tel (074) 9156 300 Fax (074) 9156 572

Mobile (086) 2554789

e-mail: eddie@abcfire.ie

KESHENDS, NEWTOWNCUNNINGHAM, CO DONEGAL

CARBON DIOXIDE(CO2) FIRE EXTINGUISHERS

TECHNICAL DETAILS

MODEL	2 COA	5 COA
CAPACITY	2 KG	5 KG
HEAD CAP	BRASS-STEEL LEVERS	
DISCHARGE	Swivel Horn	Hose & Horn
FINISH	Red Gloss Synthetic Enamel	
TEST PRESSURE (BAR)	215	215
SAFETY DISC BURST PRESSURE	185 (bar)	185 (bar)
MAX WORKING PRESSURE	150	150
FILLED WEIGHT	5 KG	12.25 KG
CYLINDER	Aluminium	Aluminium

PERFORMANCE DETAILS

DURATION (SEC)	9	15
FIRE RATING	27 B	55B
TEMPERATURE RANGE	to - 20C	to - 20C

OVERALL DIMENSIONS

HEIGHT (mm)	490	667
DIAMETER (mm)	381	475

PACKING SPECIFICATION

INDIVIDUALLY BOXED

ALL FIRE EXTINGUISHERS SUPPLIED FILLED.

A.B.C. FIRE PROTECTION