

ABC DRY POWDER

STORED PRESSURE CONTROLLED DISCHARGE EXTINGUISHERS



Controllable discharge CE Certified fire Extinguishers manufactured to I.S. EN 3, Precision engineered with brass valve and steel cylinder which is electro static paint finished to a very high standard.

CLASSES OF FIRES, A.B.C.

A

Paper, Wood, & General
Combustable Fires requiring
cooling and quenching

B

Burning liquids,
petrol, alcohol,
paint, oil, grease.

C

Gas Fires,
Methane, propane,
butane, acetylene.



A MEMBER OF:
FIRE INDUSTRY ASSOCIATION OF IRELAND

ANSUL AUTHORISED AGENT

Tel (074) 9156 300 Fax (074) 9156 572

Mobile (086) 2554789

e-mail eddie@abcfire.ie

KESHENDS, NEWTOWNCUNNINGHAM, CO DONEGAL

A.B.C. DRY POWDER FIRE EXTINGUISHERS

TECHNICAL DETAILS

MODEL	DP1	DP2	DP4	DP6	DP9
CAPACITY	1 KG	2 KG	4.5 KG	6 KG	9 KG
NECK	INTEGRAL M30 X 1.5 INTERNAL THREAD				
RING	BRASS-STEEL LEVERS WITH GAGUE				
HEAD	13mm bore black 5 braided PVC hose				
CAP	Phosphate / electro-static red enamel finish				
HOSE	Phosphate Treated				
EXTERNAL FINISH					
INTERNAL FINISH					
WEIGHT FULL	1.60 KG	2.42 KG	6.70 KG	8.50 KG	12.50 KG
TEST PRESSURE (BAR)	20	20	30	30	30
WORKING TEMPRATURE					
SPECIFICATION	Manufactured to ISEN 3 and Certified to CE 0029				

PERFORMANCE DETAILS

DISCHARGE RANGE(M)	3	4	4	4	6
DURATION (SEC)	8	10	12	12	15
FIRE RATING		13A 55B	21A 144B	27A 183B	34A 233B

OVERALL DIMENSIONS

HEIGHT (mm)	320	410	431	520	500
DIAMETER (mm)	120	130	150	152	180

PACKING SPECIFICATION

INDIVIDUALLY BOXED

ALL FIRE EXTINGUISHERS SUPPLIED FILLED WITH ABC DRY POWDER

AND CHARGED WITH OXYGEN FREE NITROGEN OVER GAS.

A.B.C. FIRE PROTECTION