

WATER

STORED PRESSURE CONTROLLED DISCHARGE EXTINGUISHERS



Controllable discharge CE Certified fire Extinguishers manufactured to I.S. EN 3, Precision engineered with brass valve and steel cylinder which is electro static paint finished to a very high standard.

CLASSES OF FIRES, A.

A

**Paper, Wood, & General
Combustable Fires requiring
cooling and quenching**



A MEMBER OF:
FIRE INDUSTRY ASSOCIATION OF IRELAND

ANSUL AUTHORISED AGENT

Tel (074) 9156 300 Fax (074) 9156 572

Mobile (086) 2554789

e-mail: eddie@abcfire.ie

KESHENDS, NEWTOWNCUNNINGHAM,
CO DONEGAL

WATER FIRE EXTINGUISHERS

TECHNICAL DETAILS

MODEL	W.90
CAPACITY	9 LITRE
NECK RING	INTEGRAL M30 X 1.5 INTERNAL THREAD
HEAD CAP	BRASS-STEEL LEVERS WITH GAGUE
HOSE	13mm bore black 5 braided PVC hose
EXTERNAL FINISH	Phosphate / electro-static red enamel finish to BS 381C RED
INTERNAL FINISH	Phosphate and Polythene
WEIGHT FULL	13 kg
TEST PRESSURE (BAR)	30
WORKING TEMPRATURE	0 to +55 C
SPECIFICATION	Manufactured to ISEN 3 and Certified to CE 0029

PERFORMANCE DETAILS

DISCHARGE RANGE(M)	6
DURATION (SEC)	60
FIRE RATING	13A

OVERALL DIMENSIONS

HEIGHT (mm)	540
DIAMETER (mm)	180

PACKING SPECIFICATION

INDIVIDUALLY BOXED	
ALL FIRE EXTINGUISHERS SUPPLIED FILLED	
AND CHARGED WITH OXYGEN	FREE NITROGEN OVER GAS.